



Switch Managed [EX3300-24T]

Product Information



24-port 10/100/1000Mbps Ethernet Switch, 4 SFP+ 1/10G uplink ports, Managed

Bhinneka Part No : SKU00113428
Price : Rp 57,761,000
Cicilan 0% : 6 x Rp 9,626,833



Harga sudah termasuk PPN 10%

BUTUH PENAWARAN? Hubungi Sales kami di 021-2929-2828 untuk membantu.

Disclaimer: Images are as represented by the manufacturer. Manufacturers occasionally make innovations in appearance without prior notice.

Overview

Juniper Networks EX3300 switch delivers a high-performance, flexible and cost-effective solution for today's most demanding converged data, voice, and video enterprise access environments. It supports Juniper Networks Virtual Chassis technology, allowing up to 10 switches to be interconnected over uplink ports and managed as a single logical device to deliver a scalable, pay-as-you-grow solution for expanding network environments.

Detail Specifications

Ports	24 port Ethernet Switch
Media interfaces	<ul style="list-style-type: none"> Connector Type: SFP/SFP+, RJ-45 Interface: Ethernet 10Base-T/100Base-TX/1000Base-T
Switching features	<ul style="list-style-type: none"> Features: IPv4 <ul style="list-style-type: none"> Maximum number of Address Resolution Protocol (ARP) entries: 4,000 Maximum number of IPv4 unicast routes in hardware: 8,000 Layer 3 redundancy: VRRP Routing protocols: RIP v1/v2, Static routing, OSPF v2, BGP v4 IP directed broadcast Features: IPv6 Management Functionality <ul style="list-style-type: none"> Neighbor discovery, system logging, Telnet, SSH, Junos Web, SNMP, Network Time Protocol (NTP), Domain Name System (DNS) Static routing
Power Supply	100 W AC
Others	<ul style="list-style-type: none"> Hardware Specifications <ul style="list-style-type: none"> Switching Engine Model: Store and forward DRAM: 1 GB with ECC Flash: 1 GB CPU: 1 GHz Uplink: Fixed 4-port uplinks which can be individually configured as GbE (SFP) or 10GbE (SFP+) ports. Dimensions (W x H x D): 43.7 x 4.4 x 31 cm Weight: 4.6 kg Packet Switching Capacities (Maximum with 64 Byte Packets): 128 Gbps Environmental Ranges

- Operating temperature: 32° to 113° F (0° to 45° C)
 - Storage temperature: -40° to 158° F (-40° to 70° C)
 - Operating altitude: Up to 10,000 ft (3,049 m)
 - Non-operating altitude: Up to 16,000 ft (4,877 m)
 - Relative humidity operating: 10% to 85% (noncondensing)
 - Relative humidity non-operating: 0% to 95% (noncondensing)
-

Bhinneka.Com Rank

Sales Rank >> #121 in Switch Managed >> #211 in SWITCH >> #232 in SWITCH AND OPTION >> #801 in NETWORK AND SECURITY SYSTEM

View Rank >> #115 in Switch Managed >> #187 in SWITCH >> #211 in SWITCH AND OPTION >> #820 in NETWORK AND SECURITY SYSTEM